EIBENSTOCK

Stirrers

You have the material and we have the adequate stirrer. No matter if painter, plasterer or bricklayer - EIBENSTOCK has the right unit, from the handy small stirrer to the mixing station Automix with 1,800 W power. Convince yourself of the robust assembly, the easy handling and the reliability and long lifetime of our stirrers.



Metal Gearbox

durable, especially for mixing

AHR 24.1

sensitive working,

less splashing

Stirring without cable up to 25 I

due to M 14 thread connection, high

concentricity, hard-

wearing, easy change



The handy cordless Stirrer is the ideal tool for every painter. Independent from a mains supply at a construction site or outside you can easily mix glue, filler,

- Low weight easy transportLarge handles non-tiring work
- Planetary gearing high torque

 Metal gearbox housing long lifetime
- □ Working time (each battery pack) depending on quantity about 30 min

Specifications	AHR 24.1
Rated speed	0 - 550 rpm
No-load speed	0 - 550 rpm
Battery pack capacity	24 V x 1.9 Ah
Max. basket diameter	100 mm
Spindle connection	M 10 female
Weight incl. battery pack	2.9 kg
Order no.	07912
Supply	2 battery packs 24 V x 1.9 Ah
quick charger	r, stirring rod (RGA 100/M 10)
Stirring rod RGA 100/M 1	0 31923
Stirring rod WGA 100/M 10	31924
Stirring rod SGA 100/M 1	0 31925
Spare battery	31903

EHR 14.1 S Set

The leightweight Stirrer up to 30 kg



is particularly suitable for tilers and painters for mixing paint, glue, tile cement etc.

- □ Large handle
 □ Twise handling easy mixing
 □ Electronic switch stepless speed control for less splashes
- Aluminium gearbox housing long lifetime
 M 14 female direct stirrer connection effective
- power transmission

 Lock-on button with protection against unintentional locking

Specifications

Supply

EHR 14.1 S

incl. Stirring Rod WG 120

Powerinput	960 W
Rated voltage	~ 230 V
Max. basket diameter	120 mm
Rated speed	0-390 rpm
No-load speed	500 rpm
Spindle connection	M 14 female
Weight	2.95 kg
Order no.	07711



EHR 15.1 SB Set

The handy Stirrer up to 40 kg



for painters, plasterers and tilers for mixing mortar, tile cement and bigger quantities of liquid media such as paint.

- Space-saving metal bow with soft grip handle handy, easy to put down, comfortable transport
- Electronic switch stepless speed control for less splashing
- Aluminium gearbox housing long lifetime
 Lock-on button for use in mixing stand with protection
 against unintentional locking

Specifications

Power input	1,000 W
Rated voltage	~ 230 V
Max. basket diameter	120 mm
Rated speed	0 - 450 rpm
No-load speed	800 rpm
Spindle connection	M 14 female
Weight	3.1 kg
Order no.	07760

Supply incl. Stirring Rod WG 120

EHR 15/2 SB Set

The universal Stirrer up to 40 kg



for painters, plasterers and tilers for mixing mortar, tile cement and bigger quantities of liquid media such as paint.

- □ Space-saving metal bow with soft grip handle handy
 - Electronic switch stepless speed control for less splashing
 - Aluminium gearbox housing long lifetime
- □ EHR 15/2 SB with 2-speed gearbox: 430 rpm for media of high viscosity (plaster, glue, mortar)
 760 rpm for media of low viscosity (paint)

Specifications

EHR 15/2 SB

EHR 15.1 SB

Power input	1,000 W
Rated voltage	~ 230 V
Max. basket diameter	120 mm
Rated speed	0-430/0-760 rpm
No-load speed	700/1,400 rpm
Spindle connection	M 14 female
Weight	3.7 kg
Order no.	07757
Supply	incl. Stirring Rod WG 120

EHR 16.1 S

The convenient tool up to 40 kg



The ideal tool for painters, plasterers and tilers. With long mixing spindle and T-shape handle for a comfortable upright working position to mix materials of high and low viscosity.

- Space-saving metal bow handle protects power tool when laid down or during transport
 soft grip less vibrations
 High-performance gearbox especially made for solutions
- mixing

 Electronic switch stepless speed control

	Lock-on button - with	protection against
- 1	unintentional locking	

Specifications	EHR 16.1 S
Power input	1,050 W
Rated voltage	~ 230 V
Max. basket diameter	120 mm
Rated speed	0 - 450 rpm
No-load speed	800 rpm
Spindle connection	M 14 female
Weight	4.1 kg
Order no.	07776
Supply	incl. Stirring Rod WG 120

EHR 20 SB Set EHR 20 RB Set

The compact Stirrer up to 50 kg



Due to the compact design, it is of particular interest for painters who require a lightweight stirrer to mix paint, but now and then also a powerful unit for larger quantities of

- Space-saving metal bow handle handy, easy to put down, comfortable transport, soft grip handle
 Aluminium gearbox housing long lifetime
- □ Protection cap with labyrinth guide
- □ EHR 20 RB soft start, thermal control, stepless speed control and constant speed

Specifications	EHR 20 SB/EHR 20 RB
Power input	1,100/1,150 W
Rated voltage	~ 230 V
Max. basket diameter	140 mm
Rated speed	0 - 580/250 - 580 rpm
No-load speed	1,000/250 - 580 rpm
Spindle connection	M 14 female
Weight	4.3 kg
Order no.	07723/07714
Supply	incl. Stirring Rod WG 135
	- 31 -

EHR 20 S Set

The robust Stirrer up to 50 kg



Due to the H-handle, this tool is particularly interesting as starting model in the building sector, for drywallers and plasterers. Preferred mixing media should be prefab plaster and mortar as well as filler.

- □ Robust H-handle
- Rubber edges protection against damage
 Electronics stepless speed control

Specifications	EHR 20 S
Powerinput	1,100 W
Rated voltage	~ 230 V
Max. basket diameter	140 mm
Rated speed	0 - 580 rpm
No-load speed	1000 rpm
Spindle connection	M 14 female
Weight	5.3 kg
Order no.	07724
Supply	incl. Stirring Rod MG 140

EHR 20/2.4 S Set

The universal Stirrer up to 50 kg



for building material of medium to high viscosity such as prefab plaster, gypsum, lime, concrete, cement, thermoinsulation material and insulants. A high reliability, long lifetime and robustness make it an indispensable work equipment for professional construction workers.

- 2-speed gearbox
- Robust H-handle

Specifications

□ Electronic switch - stepless speed control for less splashing

Power input	1.100 W
Rated voltage	~ 230 V
Max. basket diameter	140 mm
Rated speed	0 - 250/0 - 450 rpm
No-load speed	400/730 rpm
Spindle connection	M 14 female
Weight	5.6 kg

EHR 20/2.4 S

07719 Order no.

Supply incl. Stirring Rod MG 140

EHR 23/2.3 S Set

The powerful Stirrer up to 80 kg



The new powerful 1800 W motor allows a safe permant operation, even in case of high load, and mixing materials of high viscosity such as prefab mortar and plaster, cement, lime, concrete, quartz-containing epoxy resins, screed, pastes, sealing compounds as well as gypsum and granulates.

- □ 2-speed gearbox, H-handle
- □ Wide handle distance comfortable, safe guiding
- □ Electronic switch stepless speed control

Specifications	EHR 23/2.3 S
Powerinput	1,800 W
Rated voltage	~ 230 V
Max. basket diameter	160 mm
Rated speed	0 - 250/0 - 580 rpm
No-load speed	440/0 - 970 rpm
Spindle connection	M 14 female
Weight	7.2 kg
Order no.	07763
Supply	incl. Stirring Rod MG 160

EZR 21 S/EZR 21 R

Quick with two Stirring Rods up to 60 kg



The contra rotating stirring rods enable a much quicker mixing of the material. You can even achieve a homogenous consistence in case of critical material such as screed, epoxy resins, granulates, pastes as well as two and more component materials.

- □ No counter torque, easy handling
- □ Robust H-handle

Specifications

Spare rods (2 pieces)

- □ Change of stirring rods without any tool
- EZR 21 R soft start, thermal control, stepless speed control and constant speed

Power input	1,100/1,150 W
Rated voltage	~ 230 V
Total diameter of tool pair	220 mm
Rated speed	0 - 450/140 - 400 rpm
No-load speed	730/140 - 400 rpm
Weight	6.8 kg
Order no	07744/07746

EZR 21 S/EZR 21 R

31610

Order no.	07744/07746
Supply	incl. stirring rods

EIBENSTOCK

Mixing Stands



RST 10

Mixing Stand



Thanks to the Mixing Stand RST 10, bigger and smaller buckets can be fixed safely and in a matter of seconds so that a tipping over or slipping can be avoided. The user does not need any tool for that. This is especially suitable for mixing tough and sticky material, e.g. bitumen, two component materials etc.

- Metal parts galvanised rust protection
 Compact design, lightweight easy transport
 Quick fixation without any tool by means of wing nuts

 Quick adaption to different bucket sizes

Specifications

RST 10



Dimensions		670 x 360 x 36 mm
Max. size of the bucket Øx height		340 x 450 mm
Batches up to		301
Weight		6.4 kg
Order no.		09410
Supply	Mixing stand	in a cardboard box
		without bucket